

Fabric Specification Sheet

CoolView Alu

Description:

CoolView Alu helps you to create natural shade, block sun glare, control indoor temperature, save a tremendous amount of energy on cooling, lighting and heating. It is versatile with an ultra-thin layer of aluminium, highly reflective (up to 74% solar reflection) and helps to control temperature effectively. With the beautiful transparency you block sun glare without blocking the view, give the inside of your building a more open and spacious appearance enhance the comfortable living and working atmosphere.

Composition:

Composition	: 75 % PVC / 25 % PET
Construction	: woven fabric
Pattern dimensions (w x h)	: no pattern

Transparency: non-transparent, average openness factor 3 %



Transparent

Semi – Transparent

Non - Transparent

Dim out

Blackout

Special features:

Flame retardant	: BS 5867-2 type B, M2 and NFPA 701
Suitable for wet room	: no
Halogen free	: yes
UV blockage	: approx. 95 %
Recyclable	: yes


Origin:

Preferential origin EU	: yes
------------------------	-------

Dimension:

Weight per m ²	: 440 g/m ²	+/- 3%
Material thickness	: 0,55 mm	+/- 2%
Light fastness	: > 7 DIN EN ISO 105 B02 (blue scale)	
Available widths	: 240 cm	

Application:



Roller

Panel

Skylight

Accreditations:

